Product information

PI 50/10/09/2026

Motorbike 4T Bike-Additive



Description

Optimizes engine performance. Removes deposits in the fuel system, on valves, spark plugs and in the combustion chamber and prevents new deposits. - especially suitable for engines with catalytic converters . Prevents carburetor icing. Tested for catalytic converters.

Properties

- increases operational reliability
- tested for the use with catalytic converters
- reduces the risk of knocking combustion
- for carburetor and fuel-injection engines
- reduces residue
- prevents corrosion in the fuel system

Technical data

Form	liquid
Color / appearance	yellow
Odor	characteristic
Density at 20 °C	0,806 g/ml
Flash point	>61 °C
Shelf life in original sealed container	60 months

Areas of application

Add to fuel for all four-stroke engines (aspirated and injection).

Application

125 ml formulated for 15 – 20 l of fuel. Add every time you refuel.

Available pack sizes

125 ml Can sheet metal	1581 DE-EN
125 ml Can sheet metal	5918 DE-FR-IT-NL

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com