Product information

PI 54/10/21/2026

Rapid Cleaner | Brake & Parts Cleaner (Spray)



Description

A combination of selected acetone-free solvents for the rapid, efficient cleaning and degreasing of components in motor vehicles and industrial applications. The low surface tension of this product gives it excellent penetration properties, enabling it to dissolve oil, grease, resin and tar residues and contaminants easily, even in hidden areas. After the solvent has evaporated, the surface is left free of grease and residues.

Properties

- universal application
- high proportion of active components
- optimum penetration capacity
- low surface tension
- dissolves resin and tar-type residues
- controlled evaporation free of residues
- leaves no residues
- removes oil and grease-based contaminants
- contains no acetone

Technical data

Color / appearance	colourless
Base	solvent-mixture, acetone-free
Form	liquid, aerosol
Propellant	CO2
Shelf life in original sealed container	30 months

Areas of application

Automotive area:
Brakes: Drum and disk brakes, linings, shoes, cylinders, springs and pads.
Clutch: Clutch linings, pressure plate and clutch components in general.
Transmission: Automatic gear change, planet carriers, oil pump, brake bands, clutches and gearwheels.
Assembly and repair: Carburetor, gasoline pump, engine components, electrical systems such as controllers, alternator and starter. Removes oil and grease spots from floor coverings, materials and linings.

Industrial areas: For the removal of stubborn contaminants such as oil, grease, silicone residue, permanent markers, abraded rubber and wax. Ideal on sensitive surfaces and materials such as stainless steel, copper and aluminum alloys.

Comment

As this is an industrial product, it may contain traces of denatured alcohol such as isopropanol/ethanol.

Application

Spray contaminated components and allow to drain. After the solvent has evaporated, the components will be clean and free of grease.
Note: Product may attack paints and plastic components. Check for material compatibility before using!

Available pack sizes

500 ml Can aerosol	1816 AR-DE-EL-FR-NL
500 ml Can aerosol	2695 HU-PL-RO-TR
500 ml Can aerosol	2868 DA-FI-NO-SV
500 ml Can aerosol	3318 DE-EN-ES-IT-PT
500 ml Can aerosol	9525 AR-DE-EN-FR
500 ml Can aerosol	20880 JA
500 ml Can aerosol	21998 MXES

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com