Product information

Top Tec 6600 0W-20

PI 49/09/23/2026

Description

Premium low-friction motor oil based on synthetic technology. Provides optimum lubrication, excellent lubricating film stability, and minimal wear and deposits—even under extreme loads. Ideally suited for engines with start-stop system. Ensures maximum performance.



Properties

- smooth engine running
- tested for turbochargers and catalytic converters
- outstanding engine cleanliness
- excellent high and low temperature behavior
- optimum stability to aging
- optimum oil pressure under all operating conditions
- high lubrication reliability
- long engine service life
- high shear stability
- excellent wear protection

Specifications / Approvals

ACEA C5, C6 • API SQ • BMW Longlife-17 FE+ • ILSAC GF-7A • Jaguar / Land Rover STJLR.03.5006 • MB-Approval 229.71 • MB-Approval 229.72 • Opel OV 040 1547 - A20

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Chrysler MS-12145 • Fiat 9.55535-GSX • Ford WSS-M2C 947-B1 • Ford WSS-M2C 954-A1 • Ford WSS-M2C 962-A1 • Ford WSS-M2C 972-A1 • Volvo VCC C6SP • VWC 53057

Technical data

SAE class (engine oils)	0W-20 SAE J300
Density at 15 °C	0,845 g/cm³ DIN 51757
Viscosity at 40 °C	43 mm²/s ASTM D 7042-04
Viscosity at 100 °C	8,5 mm²/s ASTM D 7042-04
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -35 °C (CCS)	⩽ 6200 mPas ASTM D 5293
Viscosity index	180 DIN ISO 2909
HTHS at 150°C	⩾ 2,6 mPas ASTM D 5481

Technical data

Pour point	-48 °C DIN ISO 3016
Evaporation loss (Noack)	11 % CEC-L-10-A-93
Flash point	230 °C DIN ISO 2592
Total base number	8,3 mg KOH/g DIN ISO 3771
Sulfate ash	⩽ 0,8 % DIN 51575
Color number (ASTM)	L 3,0 DIN ISO 2049

Areas of application

For gasoline and diesel vehicles. Specially developed for the requirements of BMW, Mercedes-Benz, Opel and other manufacturers.

Application

The specifications and instructions from the unit or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

Available pack sizes

1 l Canister plastic	21410 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
5 l Canister plastic	21411 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
20 l Canister plastic	21412 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
20 l Bag-in-Box	21959 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
60 l Black plate barrel	21442 DE-EN-ES-FR-IT-PT

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com

Product information

Top Tec 6600 0W-20

PI 49/09/23/2026

Available pack sizes

205 l Black plate barrel	21443 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com