Product information
Fuel Protect Diesel

PI 11/06/11/2025



Description
Ash-free additive combination that can disperse water in the tank and thereby enable its removal from the tank. Prevents the formation of water/fuel emulsions. Effectively protects contaminated fuel systems from corrosion, reduces the formation of deposits in fuel systems and improves the lubrication of high-pressure pumps.

Properties
- outstanding corrosion protection
- disperses water in the fuel
- keeps the fuel system clean
- prevents the negative effects of water in the fuel tank
- prevents sludge formation
- good lubricating effect

Technical data

Base	additives, special carrier fluid
Color / appearance	light yellow, clear
Density at 15 °C	0,8215 g/ml
Refractive index at 20 °C	1,434
Form	liquid
Viscosity at 40 °C	<7 mm²/s
Odor	characteristic

Areas of application
Suitable for all diesel engines, specifically when used with fuels slightly contaminated with water. Prevents corrosion problems in the fuel system and thus prevents operational malfunctions. Suitable for HVO and XTL diesel.

Application
Add to fuel whenever filling up. Contents of can (300 ml) is sufficient for 60 l of fuel.

Available pack sizes

300 ml Can sheet metal	21649 EL-EN-IT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com