Product information

Top Tec 6610 0W-20

PI 26/10/13/2026

Description

Premium low-friction motor oil based on synthetic technology. Provides optimum lubrication, excellent lubricating film stability, and minimal wear and deposits—even under extreme loads. Ideally suited for engines with start-stop system. Ensures maximum performance.



Properties

- outstanding engine cleanliness
- optimum stability to aging
- tested for turbochargers and catalytic converters
- high lubrication reliability
- high shear stability
- excellent wear protection
- excellent high and low temperature behavior
- smooth engine running
- optimum oil pressure under all operating conditions
- long engine service life

Specifications / Approvals

ACEA C5 • API SQ • Ford WSS-M2C 952-A1 • Jaguar / Land Rover STJLR.03.5006 • MB-Approval 229.71 • Opel OV 040 1547 - A20

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

GM dexos D

Technical data

SAE class (engine oils)	0W-20 SAE J300
Density at 15 °C	0,845 g/cm³ DIN 51757
Viscosity at 40 °C	39 mm²/s ASTM D 7042-04
Viscosity at 100 °C	8 mm²/s ASTM D 7042-04
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -35 °C (CCS)	⩽ 6200 mPas ASTM D 5293
Viscosity index	185 DIN ISO 2909
HTHS at 150°C	⩾ 2,6 mPas ASTM D 5481
Pour point	-42 °C DIN ISO 3016

Technical data

Evaporation loss (Noack)	11 % CEC-L-10-A-93
Flash point	220 °C DIN ISO 2592
Total base number	9,5 mg KOH/g DIN ISO 3771
Sulfate ash	⩽ 0,8 % DIN 51575
Color number (ASTM)	L 3,0 DIN ISO 2049

Areas of application

For gasoline and diesel vehicles. Specially developed for the requirements of Ford, Jaguar/Land Rover, Mercedes-Benz, Opel, GM and other manufacturers.

Application

The specifications and instructions from the unit or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

Available pack sizes

1 l Canister plastic	21660 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
4 l Canister plastic	21661 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
5 l Canister plastic	21662 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
20 l Canister plastic	21663 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
60 l Black plate barrel	21664 DE-EN-ES-FR-IT-PT
205 l Black plate barrel	21666 DE-EN-ES-FR-IT-PT

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com

Product information

Top Tec 6610 0W-20

PI 26/10/13/2026

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com