Product information

PI 20/08/18/2026

Pro-Line ATF Additive



Description

A modern additive for maintaining and protecting rubber and plastic seals in automatic transmissions. Prevents and eliminates leaks caused by hardened and brittle seals. Regular preventive use with every fluid change extends the service life of transmission seals.

Properties

- maintains and regenerates rubber and plastic seals
- prevents oil loss
- increases service life
- reduces operating costs
- does not affect the friction properties of friction components

Areas of application

For maintaining and protecting rubber and plastic seals in automatic transmissions. Suitable for all torque-converter automatic transmissions, dual-clutch transmissions and CVT transmissions.

Application

Added via the additive reservoir of our Gear Tronic automatic transmission service device. Alternatively, through the automatic transmission dipstick tube or fill plug. 250 mL is sufficient for 3.5-7.5 liters of ATF and DSG transmission fluid. 500 mL is sufficient for 7.5-15 liters of ATF and DSG transmission fluid.

Available pack sizes

250 ml Tube plastic	21976 DE-EN-ES-IT-PT
250 ml Tube plastic	21984 AR-EN-FR
250 ml Tube plastic	23301 AUEN-EN
500 ml Can sheet metal	21977 DE-EN-ES-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com