Product information
Marine ATF

PI 31/09/24/2026

Description
ATF oil specially developed for the marine sector based on synthetic technology and the latest additive technology. Offers increased corrosion protection and minimizes wear compared with conventional ATF oils. The high thermal stability and excellent protective properties give it optimum resistance to aging with maximum safety reserves. Compatible with all sealing materials.



Properties
- optimum stability to aging
- universal application
- minimizes wear
- excellent corrosion protection
- highest thermal stability
- good material compatibility

Specifications / Approvals
ZF TE-ML 04D • ZF approval number ZF004927

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:
Allison C4 • Dexron II D • Dexron II E • Dexron III G • Dexron III H • Dexron TASA (Typ A/Suffix A) • Mariner • MerCruiser • Mercury

Technical data

Density at 15 °C	0,845 g/cm³ DIN 51757
Viscosity at 40 °C	36,0 mm²/s ASTM D 7042-04
Viscosity at 100 °C	7,5 mm²/s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 20000 mPas ASTM D 2983-09
Viscosity index	180 DIN ISO 2909
Pour point	-48 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592
Sulfate ash	0,1 g/100g DIN 51575
Shear stability, viscosity at 100 °C after 100 h	5,4 mm²/s DIN 51350-06-KRL/C
Color / appearance	red

Areas of application
For drives and transmissions such as reverse gears, power steering, steering systems, trimming systems, hydrostatic transmissions and hydraulic and mechanical systems that require the use of an ATF oil. Cannot be used where GL4 or GL5 oils are specified.

Application
The specifications and instructions from the unit or vehicle manufacturer must be followed.

Available pack sizes

1 l Can plastic	25066 DE-ES-FR-IT-NL
1 l Can plastic	25067 DA-EL-EN-FI-NO-SV

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com