Product information
Motorbike Speed Additive

PI 46/08/18/2026



Description

Modern ash-free combination of agents with acceleration-enhancing, cleaning, dispersing and material-protecting properties. The product has been formulated using state-of-the-art additive and fuel technologies in accordance with the requirements of today's engines, fuels and running conditions. Ensures increased driving enjoyment due to optimized performance. The engine starts easier and also runs smoother.

Properties

- higher performance gain
- improves acceleration
- cleans the fuel system
- protects fuel against oxidation and aging
- prevents corrosion in the fuel system
- prevents carburetor icing
- increases operational reliability

Technical data

Base	Additive mixture in carrier fluid
Color / appearance	light brown
Density at 15 °C	0,825 g/cm³
Flash point	>63 °C
Odor	characteristic
Form	liquid
Viscosity at 40 °C	<7 mm²/s

Areas of application

Added to the fuel of all 2-stroke and 4-stroke gasoline engines.

Application

Add to the fuel tank. For the optimum effect, add every time you refuel. Fully compatible with all gasoline grades. Contents sufficient to treat up to 20 liters of fuel.

Available pack sizes

150 ml Can sheet metal	3040 DE-EN-ES
150 ml Can sheet metal	5920 DE-EL-FR-IT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com