Product information

PI 51/10/01/2026

Top Tec ATF 1900



Description

Next-generation high-performance automatic transmission fluid based on selected base oils and modern, high-performance additives. Its reduced viscosity helps improve efficiency. The outstanding stability of the friction coefficient enables extended oil change intervals.

Properties

- excellent viscosity/temperature properties
- outstanding friction characteristics
- very good low-temperature properties
- high efficiency

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

MB 236.15

Technical data

Density at 15 °C	0,845 g/cm³ DIN 51757
Viscosity at 40 °C	19 mm²/s ASTM D 7042-04
Viscosity at 100 °C	4,4 mm²/s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	⩽ 10000 mPas ASTM D 2983-09
Viscosity index	148 DIN ISO 2909
Pour point	-51 °C DIN ISO 3016
Flash point	190 °C DIN ISO 2592
Color / appearance	blue to green

Areas of application

Developed for Mercedes-Benz 7-speed automatic transmissions of type 722.9 and 724.2 (hybrid).

Application

Shake well before use. The specifications and instructions from the assembly or vehicle manufacturer must be followed. Cannot be mixed with oils of other specifications.

Available pack sizes

1 l Can plastic	3648 DE-EN-ES-IT-PT
1 l Can plastic	21683 DA-EN-FI-NO-SV

Available pack sizes

20 l Canister plastic	3649 DE-EN-ES-IT-PT
60 l Black plate barrel	20615 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com