Product information

PI 30/09/22/2026

Pro-Line Radiator Stop Leak K



Description

Dispersion for sealing leaks in coolant circuits in passenger cars, trucks and buses. Reliably seals hairline cracks and smaller leaks. Can also be used to prevent the need for repair work on the cooling system. The solids dispersion is stabilized in carrier fluid.

Properties

- suitable for aluminum radiators
- compatible with conventional coolants and antifreezes
- no negative side effects on the water pump or heating circuit
- permanently and reliably seals hairline cracks and small leaks
- for preventive use

Technical data

Form	liquid
Color / appearance	white
Density at 20 °C	1,08 g/cm³
Solubility in water	mixable
Flash point	>100 °C

Areas of application

Used for sealing small leaks in cooling circuits of passenger motor vehicles, commercial vehicles and buses. Also suited for cooling water circuits equipped with water filters.

Comment

Store free of frost.

Contains biocides as protective agents. Contains a mixture of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1).

Application

Shake before use. Add contents to the cold cooling system and start up the heater. Then drive the vehicle for at least 10 minutes. Contents will treat up to 40 liters of coolant.

Available pack sizes

250 ml Bottle aluminum	5178 DE-EN-ES-IT-PT
250 ml Bottle aluminum	20457 BG-DE-PL

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com