Product information
Pro-Line Radiator Cleaner

PI 32/09/22/2026



Description
A concentrate specially developed for cooling systems in general but particularly those in motor vehicles. Dissolves contaminants containing oil and lime in radiators, heating systems, lines and engines. Innovative formula containing complexing agents with active cleaning agents.

Properties
- disperses sludge
- compatible with antifreeze
- good material compatibility
- chemical conversion of lime
- neutral behavior on rubber and plastics
- removes oil and grease-based contaminants

Technical data

Form	liquid
Color / appearance	colourless, unclear
Hazard class as per German VbF	none
pH value	10,31
Solubility in water	soluble
Odor	characteristic
Density at 20 °C	1,014 g/cm³

Areas of application
Suitable for all coolant circuits in passenger cars, buses and trucks.

Comment
Store free of frost.

Contains biocides as protective agents. Contains a mixture of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1).

Application
Add contents to the coolant and start up the heater. Depending on the level of contamination, run the engine at operating temperature for 10 – 30 minutes. Drain the cleaner, thoroughly flush out the cooling system with water and fill according to the manufacturer's specifications. Contents will treat up to 50 liters of coolant.

Available pack sizes

1 l Can sheet metal	5189 DE-EN-ES-IT-PT

Available pack sizes

1 l Can sheet metal	20455 BG-DE-PL

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com