Product information
Catalytic-System Cleaner

PI 27/09/15/2026



Description

Protects the catalytic converter from clogging with soot. Cleans intake valves and the combustion chamber. Improves the combustion of the fuel. Prevents corrosion in the fuel system.

Properties

- guarantees optimum combustion
- prevents corrosion in the fuel system
- protects the catalytic converter from clogging with soot
- cleans the intake tract, intake valves and combustion chamber

Technical data

Form	liquid
Color / appearance	yellow
Odor	characteristic
Density at 20 °C	0,813 g/ml
Flash point	>61 °C
Shelf life in original sealed container	60 months

Areas of application

Suitable for all gasoline engines with a catalytic converter.

Comment

Deposits in the catalytic converter based on manganese oxide cannot be removed.

Application

Pour additive into the LIQUI MOLY Pump-spray Bottle (part no. 3316). Pump up the pump-spray bottle. Establish access to the intake tract, ideally behind the turbocharger. Please note that the access must be located immediately behind the air-flow sensor. Start the engine and spray the additive into the intake tract in short bursts at medium engine speed (2,000–3,000 rpm). If the speed does not begin to fluctuate, the intervals between spraying can be lengthened. If engine speed fluctuates significantly (>700 rpm), shorten the spray duration. For fine atomization, check regularly that the pump-spray bottle has sufficient residual pressure. LIQUI MOLY cannot offer any warranty if the product is not used as specified in the product information or if dosing systems other than those indicated here are used. It is the responsibility of the user alone to verify the suitability of alternative dosing systems. For optimum cleaning of the fuel system, we recommend adding Catalytic-System Clean (Part no. 7110) to the fuel immediately after applying the additive. This will safeguard the cleanness of the complete engine system including the exhaust gas system.

Available pack sizes

300 ml Can sheet metal	8931 EL-EN-IT
300 ml Can sheet metal	21311 AR-DZAR-EN-FR
300 ml Can sheet metal	21346 AR-EN-FR

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com